



**Concrete Roads
Technology Roller Compacted
Concrete RCC
Catalin Grigore
Update June 2018**



Roller Compacted Concrete

Affordable and Sustainable Road Solution

- ✓ What is RCC
- ✓ Common Uses
- ✓ Key Elements
- ✓ Mix Design
- ✓ Structural Design
- ✓ Maintenance Cost





What is RCC?

- ✓ “Roller-Compacted Concrete (RCC) is a no-slump concrete that is compacted by high density pavers and vibratory rollers.”

- Negative Slump

- No reinforcing steel

- No finishing

- Consolidated with vibratory rollers

- ✓ Concrete pavement placed in a different way!





What is RCC?

- ✓ Consistency is stiff enough to remain stable under vibratory rollers
- ✓ Wet enough to permit adequate mixing and distribution of paste
- ✓ Typically placed with asphalt-type paver equipped with standard or high-density screed
- ✓ Final compaction obtained by a combination of passes with roller compactors





What is RCC?

- ✓ Final compaction is generally achieved within one hour of mixing.
- ✓ RCC pavements are constructed without forms, dowels, or reinforcing steel.
- ✓ Joint sawing is not always required, but when sawing is specified, transverse joints are spaced farther apart than with conventional concrete pavements.






What is RCC?

Surface of RCC

- ✓ More of an open surface texture after rolling similar an asphalt pavement surface.
- ✓ Quiet pavement due to “negative texture.”
- ✓ Can lose fine aggregate from their surface within to four years service
- ✓ Surface is treated by diamond grinding or an overlay when speed exceed 45 mph





What is RCC?

Benefits of RCC

- ✓ Primary benefit of RCC is that it can be constructed quickly and cost-effectively.
- ✓ Savings associated with RCC primarily due to:
 - ✓ Reduced Cement Content
 - ✓ Standard finisher placement
 - ✓ Reduced Construction Time
- ✓ Can be designed to have high flexural, compressive, and shear strengths, which allow it to support heavy, repetitive loads
- ✓ RCC needs no forms or finishing.
- ✓ No dowels, tie rods, or steel reinforcement



Demonstrated service life of 40+ years in harsh environments.

Benefits of RCC (cont.)

- ✓ Less concrete shrinkage and thus less cracking
- ✓ Low permeability
- ✓ Provides excellent durability and resistance to chemical attack, even under freeze-thaw conditions.
- ✓ Eliminates rutting and subsequent repairs.





What is RCC?

Potential Limitation of RCC

- ✓ Pavement edges are more difficult to compact
- ✓ Due to relatively low water content, hot-weather RCC paving requires extra vigilance to minimize water loss to evaporation.
- ✓ Due to the dryness of the RCC mixture, admixture dosage requirements can be higher for RCC than for conventional concrete.



Common Uses of RCC Pavements

- ✓ Ports/Heavy Industry
- ✓ Haul Roads
- ✓ National Roads
- ✓ Airports
- ✓ Local Streets
- ✓ Urban Streets
- ✓ Rural Roads
- ✓ Base for Overlay
- ✓ Highways





RCC Properties


- ✓ Compressive strength
- ✓ Flexural strength
- ✓ Modulus of elasticity
- ✓ Bond strength
- ✓ Freeze-thaw durability
- ✓ Shrinkage
- ✓ Permeability
- ✓ Fatigue cycles to Failure
 - ❑ Similar to PCC





RCC Properties Versus PCC

Stress Resistance RCC compare to PCC



◆ Standard Concrete

■ RCC Concrete



RCC Engineering Properties

- ✓ Compressive Strength ($f'c$) = 25 to 45 MPa
- ✓ Flexural Strength (MR) = 3.5 to 8.45 MPa

$$MR = C\sqrt{f'c}$$

where C ranges from 8 to 12

- ✓ Modulus of Elasticity (E) = 29 000 to 35 000 MPa


$$E = CE\sqrt{f'c}$$

where CE ranges from 57,000 to 67,000




Mix Design Conventional PCC versus RCC

✓ Conventional PCC



✓ Roller Compacted Concrete





Typical Mix Design

Several Methods of mix design can be used but the key criteria are specific for RCC :


- ✓ Maximum Compactness obtained at zero slump under high mechanical energy (vibration and pressure)
- ✓ Low amount of cementitious paste (less than 280 liters)
- ✓ High flexural strengths (min 5.5 MPa for standard RCC)
 - ✓ 60 to 320 kg/m³ Cementitious Material.
 - ✓ 700 to 1000 kg/m³ Sand
 - ✓ 680 to 1200 kg/m³ Coarse Aggregates
 - ✓ 80 to 125 liters/m³ Effective Water.
 - ✓ W/C Ratio usually between 0.3 – 0.45.
 - ✓ Water amount dictated by Moisture/ Density/Compaction Relationship.

Design : Minimise Slab Tensile Stress

Stress is affected by:

- ❑ Load
- ❑ Tire pressure and spacing
- ❑ Slab thickness
- ❑ Subbase support
- ❑ Concrete stiffness


Slab thickness is increased and/or
RCC strength is increased to ensure
appropriate stress ratio.






Maintenance Cost (USA)

Nominal Expenditures by Pavement Type



Total Cost Net Present Value




Asphalt is 50% more expensive than RCC throughout the life cycle of the road

Rehabilitation – Activities based on Proper Maintenance Cycles for asphalt pavements. Current year costs are inflated at 4%, Rehab costs also include other Incidental Costs (striping, mob, etc) - 40% of material costs, Traffic Control - 5% of material cost, and Engineering & Inspection - 5% of material cost



Continuous Mix Pug Mill

- High-volume applications
- Excellent mixing efficiency for dry materials
- 80 to 200+ tons/hr
- Mobile, erected on site
- Mobilization costs





Transporting & Placement





Placing Equipment

High performance pavers

- ✓ Vibrating screed
- ✓ Dual tamping bars and or pressure bars
- ✓ High initial density, 90-95%
- ✓ Reduces subsequent
- ✓ compaction
- ✓ High-volume placement (200 to 400 m³ per shift)
- ✓ Designed for harsh mixes
- ✓ Smoothest RCC surface





Compacted Edges through the use of Edging Shoes





Compaction-Final Density

- ✓ Final density is critical for strength and durability
- ✓ Compacted to 98% Modified Proctor
- ✓ Dual Steel Drum Roller
- ✓ Combination Roller
- ✓ Rubber coated steel drum roller






Concrete Curing Compound

- ✓ White-pigmented concrete curing compounds
- ✓ Apply 1 to 1.5 times the normal application rate





Typical RCC Composite Pavement Cross-Section





Madagascar Implementation 2015

- Project started March 2015





Madagascar Implementation 2015

- Trials April and May 2015





Madagascar Implementation 2015

- Official Inauguration May 2015





Madagascar First Contract 2016/2017

- ✓ First Public Road RCC approved and financed by European Union
- ✓ 250 to 350 m half road per day
- ✓ 120 heavy trucks per day
- ✓ Trucks have been allowed to circulate on RCC pavement after 7 days
- ✓ Road Specifications
 - ✓ Size : RCC 7.5 m large
 - ✓ Shoulder : RCC 0.8 m large, left and right side
 - ✓ Water Colector : RCC extruded profile



Madagascar First Contract 2016/2017

- ✓ Cost of construction 10% cheaper than equivalent asphalt road
- ✓ Fast building process
- ✓ No major quality problems
- ✓ Capital expenditure low level and equipment easy to implement
- ✓ 95 % local work force



Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar First Contract 2016/2017





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019





Madagascar MSC Container Platform 2019

